



JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 04/26/2017

Supersedes:10/19/2015

Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.
Product code : 7012-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Silicone Brake Fluid

1.3. Details of the supplier of the safety data sheet

Technical Chemical Company
P.O. BOX 139
Cleburne, Texas 76033
T 817-645-6088

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Carc. 2 H351

Full text of H statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : H351 - Suspected of causing cancer
Precautionary statements (GHS-US) : P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P308+P313 - If exposed or concerned: Get medical advice/attention
P405 - Store locked up
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Polydimethylsiloxane	(CAS No) 63148-62-9	<= 95	Not classified as hazardous
Bis(2-Ethylhexyl) Sebacate	(CAS No) 122-62-3	1 - 5	Not classified as hazardous
Tributyl Phosphate	(CAS No) 126-73-8	1 - 5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Carc. 2, H351

The exact percentage is a trade secret.

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer.
First-aid measures after inhalation	: Allow breathing of fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: If you feel unwell, seek medical advice.
Symptoms/injuries after inhalation	: Coughing. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: Itching. Red skin. Skin rash/inflammation.
Symptoms/injuries after eye contact	: Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources.
------------------	----------------------------

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Obtain special instructions. Do not handle until all safety precautions have been read and understood.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Comply with applicable regulations.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls	: Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
Personal protective equipment	: Gloves. Safety glasses. Avoid all unnecessary exposure.



Materials for protective clothing	: GIVE EXCELLENT RESISTANCE:
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Environmental exposure controls	: Avoid release to the environment.
Consumer exposure controls	: Avoid contact during pregnancy/while nursing.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Violet.
Odour	: Mild.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 206 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.97
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: > 1.3 cSt @ 100 deg C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 0 %
-------------	-------

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified as hazardous

Polydimethylsiloxane (63148-62-9)	
LD50 oral rat	> 15400 mg/kg bodyweight (Rat; Literature study)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Rabbit; Literature study)
Bis(2-Ethylhexyl) Sebacate (122-62-3)	
LD50 oral rat	> 2000 mg/kg (Rat)
Tributyl Phosphate (126-73-8)	
LD50 oral rat	1552 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	> 3100 mg/kg (Rabbit; Experimental value; Other)
LC50 inhalation rat (mg/l)	> 4242 mg/l/4h (Rat; Experimental value)

Skin corrosion/irritation	: Not classified as hazardous
Serious eye damage/irritation	: Not classified as hazardous
Respiratory or skin sensitisation	: Not classified as hazardous
Germ cell mutagenicity	: Not classified as hazardous Based on available data, the classification criteria are not met
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified as hazardous
Specific target organ toxicity (single exposure)	: Not classified as hazardous
Specific target organ toxicity (repeated exposure)	: Not classified as hazardous
Aspiration hazard	: Not classified as hazardous
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: Coughing. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: Itching. Red skin. Skin rash/inflammation.
Symptoms/injuries after eye contact	: Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.

SECTION 12: Ecological information

12.1. Toxicity

Polydimethylsiloxane (63148-62-9)	
LC50 fish 1	350 mg/l (LC50; 96 h; Pleuronectes platessa)
EC50 Daphnia 1	> 200 mg/l (LC50; 48 h; Daphnia magna)
Tributyl Phosphate (126-73-8)	
LC50 fish 2	4.2 - 11.8 mg/l (LC50; 96 h; Oncorhynchus mykiss; Static system; Fresh water)
EC50 Daphnia 2	3.65 mg/l (EC50; 48 h; Daphnia magna)
Threshold limit algae 2	2.8 mg/l (ErC50; DIN 38412-9; 72 h; Desmodesmus subspicatus; Fresh water)

12.2. Persistence and degradability

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.	
Persistence and degradability	Not established.

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Polydimethylsiloxane (63148-62-9)	
Persistence and degradability	Biodegradability in water: no data available. Forming sediments in water. Biodegradable in the soil. No (test)data on mobility of the substance available.

Bis(2-Ethylhexyl) Sebacate (122-62-3)	
Persistence and degradability	Readily biodegradable in water.

Tributyl Phosphate (126-73-8)	
Persistence and degradability	Readily biodegradable in water. No (test)data on mobility of the substance available.

12.3. Bioaccumulative potential

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.	
Bioaccumulative potential	Not established.

Polydimethylsiloxane (63148-62-9)	
Bioaccumulative potential	Not bioaccumulative.

Bis(2-Ethylhexyl) Sebacate (122-62-3)	
Bioaccumulative potential	No bioaccumulation data available.

Tributyl Phosphate (126-73-8)	
BCF fish 1	5.5 - 20 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 6 weeks; Cyprinus carpio; Semi-static system; Fresh water; Experimental value; Fresh weight)
Log Pow	4 (Experimental value; US EPA)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

Polydimethylsiloxane (63148-62-9)	
Ecology - soil	Not toxic to plants.

Tributyl Phosphate (126-73-8)	
Surface tension	0.029 N/m (20 °C)

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. . Avoid release to the environment.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): Not Regulated,

ICAO/IATA (air): Not Regulated,

IMO/IMDG (water): Not Regulated,

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not Regulated

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.

SARA Section 311/312 Hazard Classes

Delayed (chronic) health hazard
Immediate (acute) health hazard

15.2. International regulations

CANADA

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

R52/53

Full text of R-phrases: see section 16

15.2.2. National regulations

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

15.3. US State regulations

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

Polydimethylsiloxane (63148-62-9)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Bis(2-Ethylhexyl) Sebacate (122-62-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Tributyl Phosphate (126-73-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

SECTION 16: Other information

Indication of changes : Revision - See : *.

Other information : None.

Full text of H-statements:

H302	Harmful if swallowed
H315	Causes skin irritation

JOHNSEN'S DOT 5 BRAKE FLUID 12 FL.OZ.


Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H351

Suspected of causing cancer

- NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 1 - Must be preheated before ignition can occur.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

- Health : 2 Moderate Hazard - Temporary or minor injury may occur
- Flammability : 1 Slight Hazard
- Physical : 0 Minimal Hazard
- Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.